

CONCORDE

C25 Battery Charger



Dual output charger for all types and ratings of Nickel Cadmium, sealed or vented Lead Acid aircraft batteries. Isolated charge - one or two batteries. Charges all 12 and 24 volt Lead Acid batteries and 1-22 cell NiCads. Current adjustable from 0 to 25 amps. True constant current (CI) for NiCad batteries or constant potential (CP) for Lead Acid Batteries. Digital ammeter and voltmeter read charge current and voltage for either battery. Selectable charge time from 1 to 999 minutes with digital elapsed time. Operates on either 115 or 230 VAC.

D50 Discharge/Analyzer



Discharge capacity tester for all types and ratings of Nickel Cadmium, sealed or vented Lead Acid aircraft batteries. Services any voltage up to 24 volts or any type of battery. Constant current discharge adjustable from 0.1 to 50 amperes. Selectable low voltage cutoff. Selectable discharge time from 1 to 999 minutes with digital elapsed time readout. Audible alarm at end of test. Meters & timer lock-in their reading for amp-hr capacity. Accept and Fail lights for simplified go/nogo test. Operates on either 115 or 230 VAC.

12 Volt BatteryMINder® Charger/Maintainer



12-Volt 8 Amp Charger-Maintainer-Desulphator-Conditioner. A 3-stage Constant Current - Constant voltage-Float mode charger maintainer-desulphator (conditioner) that extends both the performance and life of all type/size/brands of 12-Volt batteries.

24 Volt BatteryMINder® Charger/Maintainer



24-Volt 4 Amp Charger-Maintainer-Desulphator-Conditioner. A 3-stage Constant Current - Constant voltage-Float mode charger maintainer-desulphator (conditioner) that extends both the performance and life of all type/size/brands of 24-Volt batteries..

(626) 813-1234

CONCORDE

BC5000 Battery Capacity Tester



The BC-5000 has been designed to provide the operator with accurate battery capacity testing and ease of operation.

Features include: Tests 12/24 volt lead acid batteries from 10 -50 AH, Cables included, Constant current load in 1 Amp steps, Battery powered operation, LCD display, 50 MV voltage resolution, Over temperature protection, Audio warning when capacity test is complete, 1 year warranty. Options: quick disconnect available at additional cost, Elcon connector part #4004, Cannon connector part #4010, extra cable set part #4161-60

Logic 8 Amp Battery Charger



This fully automatic 8 Amp smart battery charger is capable of charging 24 Volt NiCad or Lead Acid, military or Aviation Aircraft batteries of any rating. Unit comes with 6 ft. IEC Line cord, DC output Cable Assembly with alligator clips, DC output Cable Assembly with ring terminals (for user-supplied or optional Aircraft Battery Connector)

Activator 282 Battery Charger



Direct Connect Design - No charge cables. Microprocessor controlled, multi-step charge algorithm. 8 Amp pulses bring a deeply discharged battery up from zero volts/2 amp maximum charge. Conditioning mode top charges NiCads and rejuvenates Lead Acid. Shorted cell/overtemp protection. nonresponsive battery indication. Can be left on indefinitely - charges only when required.

CA1550 Charger/Analyzer



Charge or Discharge 12 or 24 Volt lead-acid or nickel-cadmium batteries with the easy to use, dual-featured CA1550. Charge with constant current or constant potential from 1 to 35 amps or discharge constant current from 1 to 50 amperes. This rugged unit has a digital ammeter and voltmeter as well as a digital electronic timer display.

(626) 813-1234