

MILITARY SPECIFICATION
BATTERIES, STORAGE, LEAD-ACID
GENERAL SPECIFICATION FOR

This amendment forms a part of military specification MIL-B-83769D, dated 4 April 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.4.3 Container and cover.

Change to: "The battery container shall be of nonmetallic, aluminum, steel or aluminum alloy construction. Battery covers shall be of aluminum, steel or aluminum alloy construction. If die cast aluminum is used, it shall be in accordance with QQ-A-591."

3.4.5.1 Threaded-studs.

Sentence one, change "enclosed" to "encapsulated" and "material" to "compound."

PAGE 8

3.4.9 Container cover gasket.

Sentence one, between "A" and "resilient," add: "one-piece."

3.4.11.3 Terminal connectors.

Add: "All conducting parts, internal to the battery container, shall be adequately encapsulated with an acid-resistant compound to meet the requirements of paragraph 3.5.19 when tested in accordance with 4.6.19.1 or 4.6.19.2, as applicable."

3.4.12 Inner cases, cell covers and nonmetallic containers.

Sentence four, delete and add: "Cell covers shall be constructed of a molded compound identical in compound to that used for the outside walls of the inner case or nonmetallic container. The thickness of the cell cover(s) shall be greater than or equal to the thickness of the outside walls of the inner case or nonmetallic container."

Sentence six, delete: "..., cell covers."

AMSC N/A

FSC 6140

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

PAGE 9

3.4.15 Sealing compound.

Sentence one, change "covered" to "encapsulated."

PAGE 10

3.5.2.3 Impact resistance.

Sentence one, delete: "... and cell covers."

In table, under Component, delete: "& Cell Cover."

3.5.3.4 Impact resistance.

Sentence one, delete: "... and cell covers."

PAGE 12

3.5.7 Strength of receptacle.

Sentence one, change "450 \pm 50" to "250 \pm 25."

PAGE 16

TABLE III. Qualification inspection of components and materials.

Under Part, for Impact Resistance, delete: "... and cell cover stock specimen."

PAGE 24

4.6.2.3.2 Cell covers.

Delete entire paragraph.

4.6.3.4.2 Cell covers.

Delete entire paragraph.

PAGE 25

4.6.4 Visual and mechanical.

Sentence two, change "3.5.19" to "3.5.20."

PAGE 26

4.6.7 Strength of receptacle.

Sentence two, change "450 \pm 50" to "250 \pm 25."

MIL-B-83769D
AMENDMENT 1

Custodians:
Air Force - 99
Army - ER
Navy - AS

Preparing Activity:
Navy - AS
(Project No. 6140-0633)

Review Activities:
Air Force - 11, 80
Army - AV
DLA - GS